

Tranparent Stretch Film Handrolls 25cm/20mic

Art No.:005.0110

Description

- LLDPE stretch film for Hand use or Dispenser use.

Applications

- Wrapping transport packages
- For securing loads during transport

Physical properties

	UNITS	SPECIFICATION	TOLERANCE	TESTING METHOD
THICKNESS	mμ	20	± 5%	THICKNESS GAUGE
WIDTH	mm	250	± 5%	MEASURING TAPE
DENSITY	g/cm ³	0.91-0.93	-	ASTM D-1505

Mechanical properties

	UNITS	SPECIFICATION	TOLERANCE	TESTING METHOD
TENSILE STRENGTH MD TENSILE STRENGTH TD	Mpa	27.1 21.1	10%	ASTM D 882
BREAK ELONGATION MD BREAK ELONGATION TD	%	455 605	10%	ASTM D 882
DART DROP	g	95	10%	ASTM 1709
PUNCTURE	kg	19.5	10%	FPT-750
STRETCHING LEVEL	%	250	-	FPT-750

Tolerance for:

Film net weight = ± 5%
Paper core weight = ± 10%

Condition of testing:

Temperature 26 ± 2°C
Relative humidity 57 ± 2%

Additional information (optional – delete if not applicable)

- Packaging: 12 rolls + dispenser /box, core size:2", 60boxes/pallet