

ECOPAPER

PAPERCARTONSEALING TAPE

TECHNICAL SHEET

TYPICAL APPLICATIONS

Paper carton sealing tape suitable for packaging.

ADVANTAGES AND BENEFITS

Good adhesion even in recycled cartons.
Excellent tack.
Long lasting adhesion.
Ideal for storage in extreme temperature conditions and high moisture environments.
Printable.
Hand tearable.

CONSTRUCTION

Backing: Saturated crepe paper.
Adhesive: Natural rubber and hydrocarbon resins.
Colour: Brown.



TECHNICAL DATA

ECOPAPER	METRIC
Paper Thickness	90 Micron
Total Thickness	125 Micron
Peel Adhesion	2,5 N/cm
Tensile Strength	50 N/cm
Application Temperature	2°C to 45°C
Service Temperature	-25°C to 65°C



Physical and performance characteristics shown above are obtained following tests. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 6 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.



Schelluinsestraat 70
4203 NN Gorinchem
The Netherlands



+31 (0)184 614 256



+31 (0)184 614 881



info@kortpack.nl



www.kortpack.nl



Rabobank : 1332.51.632
Iban nummer : NL83RABO0133251632
Swift code : RABONL2U



BTW nummer : NL8235.41.216 B01



KVK nummer : 54204259



Leverings- en betalingscondities
overeenkomstig de algemene
voorwaarden. Afgedrukt op de
achterzijde van dit briefpapier.
Tevens kosteloos opvraagbaar.