



| Size (mm)  | L    | W   | T    | Min Bundle Diameter | Max Bundle Diameter | Tensile Strength |
|------------|------|-----|------|---------------------|---------------------|------------------|
| 197 x 8.0  | 197  | 8.0 | 0.25 | 15                  | 60.9                | 163,1 kg         |
| 300 x 8.0  | 300  | 8.0 | 0.25 | 15                  | 93.7                | 163,1 kg         |
| 370 x 8.0  | 370  | 8.0 | 0.25 | 15                  | 116.0               | 163,1 kg         |
| 500 x 8.0  | 500  | 8.0 | 0.25 | 15                  | 157.4               | 163,1 kg         |
| 680 x 8.0  | 680  | 8.0 | 0.25 | 15                  | 214.8               | 163,1 kg         |
| 840 x 8.0  | 840  | 8.0 | 0.25 | 15                  | 265.7               | 163,1 kg         |
| 1020 x 8.0 | 1020 | 8.0 | 0.25 | 15                  | 323.0               | 163,1 kg         |
| 2000 x 8.0 | 2000 | 7.9 | 0.25 | 15                  | 635.1               | 163,1 kg         |
| 3000 x 8.0 | 3000 | 7.9 | 0.25 | 15                  | 953.6               | 163,1 kg         |

- Self-locking head design speeds installation and locks into place at any length along tie body
- Provides a strong, durable method of cable bundling
- Can be used in a wide range of indoor, outdoor, and underground (including direct burial)
- Smooth surfaces and rounded edges assures cable protection and worker safety
- Provide the ultimate support for network cables
- Material:  
304 stainless steel for general-purpose applications
- Working (Operation) Temperature: -80°C - + 538°C (-112°F - + 1000°F)
- Min Installation Temperature: -60°C (-76°F)
- Any Length is available
- Water absorption: none
- Flammability: non-flammable
- Ultraviolet resistance: excellent,
- Chemical resistance: excellent
- UL (Underwriters Laboratories) : File E258930 based newest standard UL62275
- IEC 62275 / EN 62275 compliant



|               |          |            |        |        |
|---------------|----------|------------|--------|--------|
| 01            | 1        |            |        | 180913 |
| Rev           | Qty      | Rev number | Sign   | Date   |
| Authorization | Standard | Checked    | Design |        |
| Aral Y        | Aral Y   | LIU MZ     | Fanka  |        |

## PRODUCT DRAWING

| Step          | Qty | Weight  | Ratio |
|---------------|-----|---------|-------|
|               | 1   |         |       |
| UNIT:MM       |     |         |       |
| Total page: 1 |     | page: 1 |       |

Stainless Steel Cable Ties

